



Superdraw FS

TECHNICAL DATASHEET

Superdraw FS

DESCRIPTION

Superdraw FS is a high-performance water-soluble pressing and drawing lubricant, utilising novel lubricity enhancers to provide excellent performance without chlorine. It has been specifically designed for punching, nibbling and shearing operations on sheet metal, and deep drawing of mild and stainless steels. It also helps in forming operations, as a lubricated sheet marks much less than a non-lubricated sheet.

It should be diluted at the optimum concentration for the process in question. Starting dilution should be 10% in water, but it can be used up to 100% for severe drawing applications.

Superdraw FS is based on oil-free water-soluble technology which makes subsequent removal easy with mild aqueous cleaners. The product is designed not to affect subsequent painting processes. Superdraw FS can be welded through without cleaning.

TYPICAL DATA

| | |
|-------------------------|-------------|
| <u>Concentrate</u> | |
| Appearance | Amber Fluid |
| Specific Gravity | 1.050 |
| Mineral Oil Content % | Nil |
| <u>Emulsion</u> | |
| Appearance | Translucent |
| pH at 10% | 8.8 |
| Reichert Wear Test @10% | |
| Wear ratio, % | 15 |
| Noise reduction, m | 9 |

ADVANTAGES

- Easy stripping
- Longer tool life
- High film strength for metal forming
- Easier degreasing prior to painting
- Can be used on carbon, steel, copper, brass and aluminium
- No stickiness due to tacky oils

FIRE RISKS & HAZARDS

- Use of highly inflammable and hazardous solvents is not required
- No irritating smoke during subsequent operations
- No oil mist